

DESCRIPTION

Patented PVC tight fibered cotton composite corner bead that is 3" wide, 1-1/2" flanges, .026" thick and comes in 8', 9', 10' and 12' lengths. Big-Stick installs fast and clean for outside 90° corners and is ideal for high traffic areas where bumps and dents are likely to occur. Easier to install than metal corner bead; Big-Stick resists dents and paint chipping, cuts easily with a utility knife or scissors, applies with all-purpose joint compound, and will not rust. protective laminated nose, is extremely strong and bounces back after impact.

ADVANTAGES

- Vertical or horizontal outside 90° corners.
- High traffic areas where bumps and dents to corners most commonly occur.
- Resists dents and paint chipping, and provides a beautiful corner without fuzz-up during finishing and sanding.
- Spans over large gaps without shrinking.
- Easiest corner bead on the market to install or repair.
- Second coat of compound can be applied immediately – very light skim coat to finish.

WARRANTY

Strait-Flex products are backed by a lifetime warranty. When applied to a sound structure, built on a permanent foundation using recommended application techniques, we warrant that these products will not edge-crack for the lifetime of the structure. Not recommended where structural movement may occur. Contact Strait-Flex International Inc for complete details.

DIRECTIONS

- Measure wall height and subtract 1/2". Measure and cut Big-Stick using a scissors or utility knife.
- With a 4" or 5" taping knife, apply a smooth, liberal coat of all-purpose compound to corner.
- Press Big-Stick into the wet compound. Adjust if necessary to create a straight line.
- Wipe down tight with taping knife using a little additional pressure on the outer edges of Big-Stick. Immediately apply a light skim coat of compound over surface. Wipe down tight and smooth. Let dry completely over several hours or overnight.
- With a 6" or 8" taping knife, apply your final coat of compound feathering the compound beyond previous coat. Let dry completely over several hours or overnight
- Sand lightly with 120 grit sandpaper. Big-Stick will not fuzz-up like paper or mesh tapes.

STORAGE

Store in dry place protected from moisture.

SUBMITTAL APPROVALS

JOB NAME

CONTRACTOR

DATE

