
DESCRIPTION

Patented PVC fiber composite material patch measures 5" in diameter, a center cut-out of 2-1/4", and .013" thickness. Pre-cut to fit standard sprinkler heads and PVC pipes, Head-Patch will not sag on large ceiling mis-cuts. Head-Patch will not fuzz-up during sanding.

ADVANTAGES

- Mis-cut or damaged areas around sprinkler pipe holes.
- Corrects cutouts that were made too large
- Easily installs using standard drywall compounds.

WARRANTY

Strait-Flex products are backed by a lifetime warranty. When applied to a sound structure, built on a permanent foundation using recommended application techniques, we warrant that these products will not edge-crack for the lifetime of the structure. Not recommended where structural movement may occur. Contact Strait-Flex International Inc for complete details.

DIRECTIONS

- To apply, lightly sand area to be repaired.
- Apply drywall compound 1/8"-1/4" thick directly to back of patch.
- Place patch over center of repair and wipe down flat to wall using joint knife.
- Immediately skim-coat patch and let dry.
- Apply second coat, let dry, and sand. Compound that remains on backside of Head-Patch makes patch very rigid in the damaged area.

STORAGE

Store in dry place protected from moisture.

SUBMITTAL APPROVALS

JOB NAME

CONTRACTOR

DATE

