

DESCRIPTION

Patented PVC-tight fibered cotton composite corner tape that is 4" wide, .02" thick and comes in 100' rolls. Strait-Flex Huge has a recess running the length of tape, which makes folding quick and is adjustable to any angle. Material is very stable with temperature changes and is flexible while maintaining it's rigidity when wet.

ADVANTAGES

- Huge straightens large framing irregularities, spans extra wide gaps and is ideal for obtuse angles, off angles, and outside 90° corners.
- Forms easily to all angles and corners.
- Will not shrink, blister, tear, sag or wrinkle.
- Water resistant and rustproof.
- Saves 25-50% on installation time.
- Material can be second coated immediately.
- Solid rolls ensure no waste or damage in transit or in rough site conditions.
- Does not require fasteners, stapling, or any special tools.
- Will not edge crack or dent like traditional nail-on metal corner beads.
- Requires very light fill coat to finish product.

WARRANTY

Strait-Flex products are backed by a lifetime warranty. When applied to a sound structure, built on a permanent foundation using recommended application techniques, we warrant that these products will not edge-crack for the lifetime of the structure. Not recommended where structural movement may occur. Contact Strait-Flex International Inc for complete details.

DIRECTIONS

- Cut Strait-Flex's HUGE to desired length and trim ends at 45-degree angles. Fold HUGE in half at center crease with print size facing each other. For outside corners, fold more than the desired angle with print side facing wall. For inside corners, fold less than desired angle with print side facing out.
- Apply all-purpose compound to corner. Press HUGE into the wet compound, adjust to create a straight line, and wipe down with a taping knife. A second coat can be applied immediately. Let dry completely over several hours or overnight.
- With a 6" or 8" taping knife, apply your final coat of compound feathering the compound beyond previous coat. For inside corners, a very light coat of compound is all that's needed. Let dry completely over several hours or overnight.
- Sand lightly with 120 grit sandpaper. HUGE will not fuzz-up like paper or mesh tapes.

STORAGE

Store in dry place protected from moisture.

SUBMITTAL APPROVALS

JOB NAME

CONTRACTOR

DATE

