
DESCRIPTION

Patented PVC fiber composite material patch measures 6" diameter and .013" thickness. Outperforming metal patches, Ultra-Patch quickly repairs damage to drywall. Ultra-Patch will not fuzz-up during sanding. One Ultra-Patch repairs holes up to three inches in diameter.

ADVANTAGES

- Outperforms metal patches.
- Quickly repairs damage to drywall.
- The most economical and permanent way to repair drywall.
- Easily installs using standard drywall compounds.

WARRANTY

Strait-Flex products are backed by a lifetime warranty. When applied to a sound structure, built on a permanent foundation using recommended application techniques, we warrant that these products will not edge-crack for the lifetime of the structure. Not recommended where structural movement may occur. Contact Strait-Flex International Inc for complete details.

DIRECTIONS

- To apply, lightly sand area to be repaired.
- Apply drywall compound 1/8"-1/4" thick directly to back of patch.
- Place patch over center of repair and wipe down flat to wall using joint knife.
- Immediately skim-coat patch and let dry.
- Apply second coat, let dry, and sand. Compound that remains on backside of Perma-Patch makes patch very rigid in the damaged area.

STORAGE

Store in dry place protected from moisture.

SUBMITTAL APPROVALS

JOB NAME

CONTRACTOR

DATE

